

just led+lights

LED Tape, Indoor and Waterproof

Specifications

1. Index
2. Regular LED Tape (1.5w/ft.) 24w/16ft. roll, indoor
3. Regular LED Tape (1.5w/ft.) 24w/16ft. roll, waterproof
4. Side emitting LED tape (1.5w/ft.) 24w/16ft. roll
5. Very high output LED tape (4.5w/ft.) 72w/16ft. roll, indoor
RGB color-changing tape, indoor
6. Very high output LED tape (4.5w/ft.) 72w/16ft. roll, waterproof
RGB color-changing tape, waterproof
7. High output LED tape (2.3w/ft.) 36w/16ft. roll, indoor
8. High output LED tape (2.3w/ft.) 36w/16ft. roll, waterproof
9. Connectors for LED tape
10. Other types of available tape
11. Power Supplies

just led+lights

Regular LED tape (1.5w/ft.) 24w/16 ft. roll, indoor

3528 LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS-3528-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	1.5w/ft.	L=16.4ft W=3/8" D=1/8"	1,000-1,200 mcd	Indoor Use
JLAL-FS-3528-Y	Yellow						1,000-1,200 mcd	
JLAL-FS-3528-G	Green						1,500-2,000 mcd	
JLAL-FS-3528-B	Blue						500-600 mcd	
JLAL-FS-3528-W	White						1,600-2,000 mcd	
JLAL-FS-3528-WW	Warm White						1,600-2,000 mcd	

Features

- Uses 3528 SMD LED as light source, providing maximum brightness and uniformity
- Uses flexible FPC circuit board for easy bending
- Has 3pcs LED for each loop and can be cut every 50mm
- Works at 12VDC for low power consumption
- Designed with two soldering pans for convenient connections

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

just led+lights

Regular LED tape (1.5w/ft.) 24w/16 ft. roll, waterproof sleeve

3528 Waterproof LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FSW-3528-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	1.5w/ft.	L=16.4ft W=3/8" D=1/8"	1,000-1,200 mcd	Outdoor Use
JLAL-FSW-3528-Y	Yellow						1,000-1,200 mcd	
JLAL-FSW-3528-G	Green						1,500-2,000 mcd	
JLAL-FSW-3528-B	Blue						500-600 mcd	
JLAL-FSW-3528-W	White						1,600-2,000 mcd	
JLAL-FSW-3528-WW	Warm White						1,600-2,000 mcd	

Features

- Uses 3528 SMD LED as light source, providing maximum brightness and uniformity
- Uses flexible FPC circuit board for easy bending
- Has 3pcs LED for each loop and can be cut every 50mm
- Works at 12VDC for low power consumption
- Designed with two soldering pans for convenient connections

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin lighting
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

just led+lights

Side Emitting LED tape (1.5w/ft.) 24w/16 ft. roll, indoor

335 LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS-335-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	1.5w/ft.	L=16.4ft W=3/8" D=1/8"	1,000-1,200 mcd	Indoor Use
JLAL-FS-335-Y	Yellow						1,000-1,200 mcd	
JLAL-FS-335-G	Green						1,500-2,000 mcd	
JLAL-FS-335-B	Blue						500-600 mcd	
JLAL-FS-335-W	White						1,600-2,000 mcd	
JLAL-FS-335-WW	Warm White						1,600-2,000 mcd	

DC24V working voltage is also available

Features

- Uses 335 side emitting LED as light source, providing maximum brightness and uniformity
- Uses flexible FPC circuit board for easy bending
- Has 3pcs LED for each loop and can be cut every 50mm
- Works at 12VDC for low power consumption
- Designed with two soldering pans for convenient connections

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

1210 Mission Drive, Suite 202, Solvang, CA 93463
Tel (805) 686-4100 Fax (805) 686-0700

just led+lights

Very High Output LED tape (4.5w/ft.) 72w/16 ft. roll, indoor
RGB Color Change LED tape, indoor

5050 LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS60-5050-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	4.5w/ft.	L=16.4ft W=1/2" D=1/8"	3,000-4,000 mcd	Indoor Use
JLAL-FS60-5050-Y	Yellow						3,000-4,000 mcd	
JLAL-FS60-5050-G	Green						4,000-5,000 mcd	
JLAL-FS60-5050-B	Blue						2,500-3,500 mcd	
JLAL-FS60-5050-W	White						4,800-5,800 mcd	
JLAL-FS60-5050-WW	Warm White						4,800-5,800 mcd	

5050 RGB LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS60-5050-RGB	R G B	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	4.5w/ft.	L=16.4ft W=1/2" D=1/8"	2,500-3,500 mcd	Indoor Use

Features

- Uses 5050 (3 chips) SMD LED as light source, providing maximum brightness and uniformity
- Uses FPC circuit board for easy bending (0.15mm thickness)
- Has 3pcs LED (DC12V) or 5 pcs LED (DC24V) for each loop and can be cut every 50mm or 100mm
- Works at 12VDC or 24VDC for low power consumption
- Designed with two soldering pans for convenient connections

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

just led+lights

Very High Output LED tape (4.5w/ft.) 72w/16 ft. roll, waterproof
RGB Color Change LED tape, waterproof

5050 Waterproof LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS60W-5050-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	4.5w/ft.	L=16.4ft W=1/2" D=1/8"	3,000-4,000 mcd	Indoor Use
JLAL-FS60W-5050-Y	Yellow						3,000-4,000 mcd	
JLAL-FS60W-5050-G	Green						4,000-5,000 mcd	
JLAL-FS60W-5050-B	Blue						2,500-3,500 mcd	
JLAL-FS60W-5050-W	White						4,800-5,800 mcd	
JLAL-FS60W-5050-WW	Warm White						4,800-5,800 mcd	

5050 Waterproof RGB LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS60W-5050-RGB	R G B	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	4.5w/ft.	L=16.4ft W=1/2" D=1/8"	2,500-3,500 mcd	Indoor Use

DC24V working voltage is also available, with cuttable unit at 4"/6 LEDs

Features

- Uses 5050 (3 chips) SMD LED as light source, providing maximum brightness and uniformity
- Uses FPC circuit board for easy bending (0.15mm thickness)
- Has 3pcs LED (DC12V) or 5 pcs LED (DC24V) for each loop and can be cut every 50mm or 100mm
- Works at 12VDC or 24VDC for low power consumption
- Designed with two soldering pans for convenient connections
- Uses special silicone tube to hold the flexi-strip light inside

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

1210 Mission Drive, Suite 202, Solvang, CA 93463
Tel (805) 686-4100 Fax (805) 686-0700

just led+lights

High Output LED tape (2.3w/ft.) 36w/16 ft. roll, indoor

3528 LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FS-3528-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	2.3w/ft.	L=16.4ft W=3/8" D=1/8"	1,000-1,200 mcd	Indoor Use
JLAL-FS-3528-Y	Yellow						1,000-1,200 mcd	
JLAL-FS-3528-G	Green						1,500-2,000 mcd	
JLAL-FS-3528-B	Blue						500-600 mcd	
JLAL-FS-3528-W	White						1,600-2,000 mcd	
JLAL-FS-3528-WW	Warm White						1,600-2,000 mcd	

Features

- Uses 3528 SMD LED as light source, providing maximum brightness and uniformity
- Uses flexible FPC circuit board for easy bending
- Has 3pcs LED for each loop and can be cut every 50mm
- Works at 12VDC for low power consumption
- Designed with two soldering pans for convenient connections

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

just led+lights

High Output LED tape (2.3w/ft.) 36w/16 ft. roll, waterproof

3528 Waterproof LED Flexi-Strip

Model	LED Color	LED Space/Number	Cuttable Unit/LEDs	Input Voltage	Power/Foot	Overall Size	LED Intensity	Remark
JLAL-FSW-3528-R	Red	0.63" 60LEDs/39"	1.97" 3 LEDs	12VDC	1.5w/ft.	L=16.4ft W=3/8" D=1/8"	1,000-1,200 mcd	Outdoor Use
JLAL-FSW-3528-Y	Yellow						1,000-1,200 mcd	
JLAL-FSW-3528-G	Green						1,500-2,000 mcd	
JLAL-FSW-3528-B	Blue						500-600 mcd	
JLAL-FSW-3528-W	White						1,600-2,000 mcd	
JLAL-FSW-3528-WW	Warm White						1,600-2,000 mcd	

Features

- Uses 3528 SMD LED as light source, providing maximum brightness and uniformity
- Uses flexible FPC circuit board for easy bending
- Has 3pcs LED for each loop and can be cut every 50mm
- Works at 12VDC for low power consumption
- Designed with two soldering pans for convenient connections
- Uses special silicone tube to hold the flexi-strip light inside

Application

- Architectural decorative lighting
- Archway, canopy and bridge edge lighting
- Amusement park, theater and aircraft cabin
- Mood lighting
- Emergency hallway & exit path lighting
- Auditorium walkway lighting
- Stairway accent lighting
- Concealed lighting
- Backlighting for signage letters
- Channel letter lighting
- Cove lighting

1210 Mission Drive, Suite 202, Solvang, CA 93463
Tel (805) 686-4100 Fax (805) 686-0700

just led+lights

Other Types of Available Tape

- I. Regular Output tape – Silicone Covered
- II. Very High Output tape – Silicone Covered
- III. High Output tape – Silicone Covered
- IV. Rigid Strips

just led+lights

LED DC Power Supplies

Power supplies are magnetic and are DC made for LED Tape. There are various sizes and wattages allowing the tape to dim with the use of a magnetic dimmer.

- A. Model JLAL-35-I-12VDC = 35w indoor LED DC power supply
Size = 5.5" L x 2" W x 1.5" D
Voltage = 120V primary, 12VDC secondary magnetic
- B. Model JLAL-60-IO-12VDC = 60w indoor & outdoor LED DC power supply
Size = 8.0" L x 3" W x 2.75" D
Voltage = 120V primary, 12VDC secondary magnetic
- C. Model JLAL-100-IO-12VDC = 100w indoor & outdoor LED DC power supply
Size = 9.0" L x 3.5" W x 3.4" D
Voltage = 120V primary, 12VDC secondary magnetic
- D. Model JLAL-150-IO-12VDC = 150w indoor & outdoor LED DC power supply
Size = 9.0" L x 4" W x 3" D
Voltage = 120V primary, 12VDC secondary magnetic