



## SPECIFICATIONS

Watts	4.5W/FT
Lumens	476LM/FT (at 4000K, IP20)
Efficacy	115LM/W
Light Source	2835-210 SMD LED
LED Chips	1050 pcs/roll
CRI	90
Input	24VDC
Dimming	Dimmable
Temperature	2400K, 2700K, 3000K, 4000K, 5000K 6000K
Beam Spread	120°
Dimensions	5M Roll (16.4FT) IP20: 10mm W x 1.4mm H IP62: 10mm W x 3.0mm H IP65: 12.5mm W x 4.3mm H IP68: 12.5mm W x 5.3mm H
Cutttable	Every 1.31"
Material	Flexible FPC with 3M VHB Adhesive (IP20 & IP62 only)
IP Rating	IP20: Suitable for Indoor/Dry application IP62: Suitable for Damp applications IP65: Suitable for Outdoor/Wet applications IP68: Suitable for Submersible applications
Certifications	cUL, CE, RoHS
Lifespan	50,000+ Hours
Warranty	5 Years

IP20



IP62



IP65



IP68



## ORDERING GUIDE

Part	Temperature	IP Rating
<b>JLAL-STR-01-72W</b>	<b>24K:</b> 2400K <b>40K:</b> 4000K	<b>IP20:</b> IP20
	<b>27K:</b> 2700K <b>50K:</b> 5000K	<b>IP62:</b> IP62
	<b>30K:</b> 3000K <b>60K:</b> 6000K	<b>IP65:</b> IP65
		<b>IP68:</b> IP68

LUMEN CHART

Temperature	IP Rating	LM/FT
● 2700	20	387
● 3000	20	402
● 4000	20	476
● 5000	20	460
● 6000	20	476
● 2700	62	323
● 3000	62	335
● 4000	62	396
● 5000	62	381
● 6000	62	393
● 2700	65	323
● 3000	65	335
● 4000	65	396
● 5000	65	381
● 6000	65	393
● 2700	68	323
● 3000	68	335
● 4000	68	396
● 5000	68	381
● 6000	68	393

LIGHT DISTRIBUTION

