















Watts 11W

Lumens 1364-1426LM

CRI 80, 90

Input 120-277V

Dimming Non-Dimming

Temperature 3000K, 4000K, 5000K

Beam Spread 15°, 30°, 45°

Dimensions 5.51"L x 3.5"W x 7.51"H

Material Aluminum & Tempered Glass

Finish Black, White, Gray, Silver, Bronze

IP Rating IP65


Certifications ETL, CE


Applications Ground, Wall

Features 210° Rotation, 360° Light Disbursement

Lifespan 30,000+ Hours

Warranty 5 Years









ORDERING GUIDE

Part	Temperature	CRI	Beam Spread	Cover Frame	Gear Box	Finish
JLAL-004-SPF-02	30K : 3000K	80 : 80CRI	15 : 15°	CR: Ring	R: Round	BK: Black
	40K : 4000K	90 : 90CRI	30 : 30°	CV: Angled Visor	T: Trapezoid	WH: White
	50K : 5000K		45 : 45°	CF: Full Visor		GY : Gray
						SI · Silvor

SL: Silver

Options BZ: Bronze

GS: Ground StakeTS: Tree StrapH: Honeycomb

M: Marine Ambient Corrosion Resistance













ACCESSORIES

COVER FRAME







Ring

Full Visor

Angled Visor

GEAR BOX





Round

Trapezoid

MOUNTING





Ground Stake

Tree Strap