



SPECIFICATIONS

| | |
|----------------|--|
| Watts | 6W/FT |
| Lumens | 476-517LM/FT |
| Light Source | 3528-240 SMD LED |
| CRI | 90 |
| Input | 12VDC, 24VDC |
| Dimming | 0-10V |
| Temperature | 2700K, 3000K, 4000K |
| Beam Spread | 120° |
| Dimensions | 5M (16.4') Length IP20: 10mm W x 2.3mm H IP65: 10mm W x 3.2mm H IP68: 12.5mm W x 5.3mm H |
| Cuttable | Every 1.97" (12V), Every 3.94" (24V) |
| Material | Flexible FPC with 3M VHB Adhesive Backing |
| IP Rating | IP20: Suitable for Indoor/Dry application IP65: Suitable for Outdoor/Damp applications IP68: Suitable for Wet applications |
| Certifications | cUL (Strip), cETL (Driver), CE, RoHS |
| Lifespan | 35,000+ Hours |
| Warranty | 3 Years |

IP20



IP65



IP68



ORDERING GUIDE

| Part | Temperature | Voltage | IP Rating |
|--------------------|-------------|-----------|------------|
| JLAL-STR-96W-KIT-4 | 27K: 2700K | 12: 12VDC | IP20: IP20 |
| | 30K: 3000K | 24: 24VDC | IP65: IP65 |
| | 40K: 4000K | | IP68: IP68 |

KIT DETAILS

1_{ea} 5M Length of LED Strip with 1M Jumper Cable at each end*



1_{ea} 100W Dimmable Power Supply with 60in Plug



2_{ea} 2M Jumper Cable with Connectors at each end*



2_{ea} Cable to Cable Connector*



2_{ea} Cable to LED Strip Connector*



2_{ea} LED Strip to LED Strip Connector*



6_{ea} Cable Clips*



* Includes 3M VHB Adhesive Backing