



## SPECIFICATIONS

Watts	10W, 15W
Lumens	10W: 644-575LM 15W: 661-577LM
CRI	80
Input	120V
Dimming	TRIAC
Temperature	3000K, 4000K
Beam Spread	20°, 40°, 60°, 45°x23°
Dimensions	19.68"L x 2.95"W x 6.45"H
Material	Die Cast Aluminum & High Intensity Tempered Glass, Thermoset Powder Coat finish.
Shroud	Angled Retractable Shroud, Open Retractable Shroud
Finish	Black, White, Gray, Silver, Bronze
IP Rating	IP65
Certifications	cETL, CE
Applications	Ground, Wall
Lifespan	30,000+ Hours
Warranty	5 Years

## ORDERING GUIDE

Part	Watts	Temperature	Beam Spread	Shroud	Finish	Options
JLAL-004-SPF-010	10: 10W	30K: 3000K	20: 20°	NS: No Shroud	BK: Black	H: Honeycomb Louver
	15: 15W	40K: 4000K	40: 40°	AS: Angled Shroud	WH: White	M: Marine Ambient
			60: 60°	OS: Open Shroud	GY: Gray	Corrosion Resistance
			4523: 45°x23°		SL: Silver	
					BZ: Bronze	